

qmail / sendmail / MTA

instalace dnscache / qmail / imap - Mandriva 2006

1) instalace a konfig qmail

.RPM pro MDK 9.2 fungují i v novějších verzích (Mandriva 2006), nainstalovat:

```
daemontools-0.76-6rph.i586.rpm  
ucspi-tcp-0.88-7rph.i586.rpm  
djbdns-extcache-1.05-19rph.i586.rpm  
qmail-1.03-25.92rph.i586.rpm
```

2) instalace a konfig imap

```
urpmi courier-imap courier-imap-pop courier-imap-mysql
```

vytvořit mysql databázi imap, tabulka passwd:

```
CREATE DATABASE `imap` DEFAULT CHARACTER SET utf8 COLLATE utf8_czech_c  
i;
```

```
CREATE TABLE passwd (  
  id char(128) NOT NULL default '',  
  crypt char(128) NOT NULL default '',  
  clear char(128) NOT NULL default '',  
  name char(128) NOT NULL default '',  
  uid int(10) unsigned NOT NULL default '65534',  
  gid int(10) unsigned NOT NULL default '65534',  
  home char(255) NOT NULL default '',  
  maildir char(255) NOT NULL default '',  
  defaultdelivery char(255) NOT NULL default '',  
  quota char(255) NOT NULL default '',  
  KEY id (id)  
) TYPE=MyISAM;
```

```
INSERT INTO passwd VALUES ('jmeno.prijmeni', ENCRYPT('heslo'), '', '', 500  
, 500, '/home/prijmeni', '', '', '');
```

nastavit v /etc/courier/authmysqlrc mysql server, user, pass, database, table,...

```
chkconfig --level 3 qmail on
```

```
chkconfig --level 3 courier-imap on
```

Unique solution ID: #1068

Author: Daniel

qmail / sendmail / MTA

Last update: 2007-01-01 15:34